

CEILING

3 COLOUR IN 1 WALL & CEILING LIGHT



Key Features:

- Die Cast Aluminium & PMMA Diffuser
- IP54
- Energy Efficient
- Up to 2350lm output through opal diffuser
- CCT Selectable ~ 3000, 4200 & 6000K
- Microwave & Emergency versions available



SPECIFICATION



Part Code	IN-C 400R-3C	IN-C 400R-3C-MS	IN-C 400R-3C-EM	IN-C 400R-3C-MS-EM
Input Voltage	220~240VAC	220~240VAC	220~240VAC	220~240VAC
Power	24W	24W	24W	24W
Power Factor	>0.95	>0.95	>0.95	>0.95
Lumens	2100 / 2350 / 2230lm	2100 / 2350 / 2230lm	2100 / 2350 / 2230lm	2100 / 2350 / 2230lm
Colour (K)	3000K, 4200K, 6000K (CCT Selectable)			
Lumen Field Angle	120°	120°	120°	120°
Working Temperature	-30°C ~ +40°C	-30°C ~ +40°C	-30°C ~ +40°C	-30°C ~ +40°C
CRI	80	80	80	80
Weight	945g	945g	945g	945g
Dimensions	Ø400 x 122mm	Ø400 x 122mm	Ø400 x 122mm	Ø400 x 122mm



Mechanical Diagrams



INNER LED

12b Homecroft Road, Sydenham, SE26 5QG
W innerled.co.uk E sales@innerled.co.uk
Tel 01883 592249