

DIFFUSED ON BOARD
FLEXIBLE LED TAPE

TUNEABLE DOB

INNER LED

12b Homecroft Road, Sydenham, SE26 5QG
W innerled.co.uk E sales@innerled.co.uk
Tel **01883 592249**



16W/M



up to
800LM/M



IP20



IP67



Recycleable
Cardboard



Tuneable



>90Ra



50mm
Cut Points



Flicker Free

2700K

4000K

6500K

FEATURES

- CCT Tuneable 2700K ~ 6500K
- Industrial grade adhesive backing tape
- Supplied on cardboard reels
- High CRI >90Ra
- Working temperature -20°C - +40°C
- High efficacy
- 3 years warranty

SPECIFICATIONS

Voltage	24VDC	24VDC
Power Consumption	16W/M	16W/M
Lumen Output	720~800LM/M	720~800LM/M
Efficacy	50LM/W	50LM/W
Tone (CCT)	2700K ~ 6500K	2700K ~ 6500K
LED/metre	640	640
LED Pitch	1.54mm	1.54mm
Cut Points	50mm	50mm
CRI	>90Ra	>90Ra
IP Rating	20	67
Dimensions	5000 x 10 x 1.6mm	5000 x 12 x 1.8mm



2700K



4000K



6500K

DIFFUSED ON BOARD
FLEXIBLE LED TAPE

TUNEABLE DOB

INNER LED

12b Homecroft Road, Sydenham, SE26 5QG
W [innerled.co.uk](mailto:sales@innerled.co.uk) E sales@innerled.co.uk
Tel 01883 592249

COMPATIBILITY



CONTROL METHODS

- Remote Control - CCT-RF-RCX (with a receiver CCT-RF-3X5A)
- Bluetooth (Apps, Voice Control) - BLE-15A-CCT
- Hard-wired wall-mounted controller - CCT-4X5A-WM

MECHANICAL DIAGRAM

